

X6 12. (Amended) A horizontal burning HID arc tube having a pair of spaced apart electrodes and canoe-shaped lower portion.

X7 17. (Amended) A horizontal burning double-ended HID arc tube having a pair of spaced apart electrodes, an upper portion longitudinally conforming generally between said electrodes to the shape of the arc to be drawn therebetween in the operation of the arc tube, and flattened bottom.

X8 20. (Amended) A horizontal burning double-ended HID arc tube having a pair of spaced apart electrodes, said electrodes are tilted downwardly toward each other.

X9 22. (Amended) The arc tube of Claim 20 wherein the sides of said arc tube progressively narrow from the center of said arc tube towards both ends of said arc tube.

X9 23. (Amended) A horizontal burning HID arc tube having a pair of spaced apart electrodes and a lower portion having a flattened bottom, the distance from said electrodes to said bottom being less than the distance from electrodes to the upper portion of said arc tube.

26. (Amended) The arc tube of Claim 23 wherein the upper portion joins said lower portion below said electrodes.

X10 27. (Amended) A horizontal burning HID arc tube having a pair of spaced apart electrodes, a circular cross-section upper portion and a lower portion with a flattened bottom, the distance from said electrodes to said flattened bottom being less than the distance from electrodes to the upper portion thereof.

X11 29. (Amended) The arc tube of Claim 27 wherein said upper portion joins said lower portion below said electrodes.

A¹¹ cont
30. (Amended) A horizontal burning HID arc tube having a pair of spaced apart coaxial electrodes, a circular cross-section upper portion and a lower portion having a flattened bottom, said upper portion joins said lower portion below the elevation of said electrodes.

A¹²
32. (Amended) A horizontal burning HID arc tube having a pair of spaced apart coaxial electrodes, an upper portion longitudinally conforming generally between said electrodes to the shape of the arc to be drawn therebetween in the operation of the arc tube, and flattened bottom to thereby reduce the temperature differential in the arc tube walls.

33. (Amended) The arc tube of Claim 32 wherein the lowest elevation of said lower portion is in the longitudinal center of the arc tube.

A¹³
41. (Amended) An arc tube blank comprising an enlarged light emitting chamber intermediate tubular ends of the same diameter, said chamber having a lower portion with a flattened bottom.

A¹⁴
46. (Amended) The method of Claim 41 wherein the bottom of said chamber is flattened in an area between about 20 and about 80 percent of the maximum length of said chamber.

47. (Amended) The arc tube of Claim 46 wherein the bottom of said chamber in the longitudinal center thereof is flattened over a distance between about 50 and about 60 percent of the length of said chamber.

A¹⁵
50. (Amended) The arc tube blank of Claim 41 wherein the height of said chamber is the greatest at the longitudinal center of said chamber and progressively more narrow towards the ends of said chamber.